

8-OSOVINSKI NISKOPODNI SPECIJALNI TERETNI VAGON ZA PRIJEVOZ KAMIONA S PRIKOLICOM

8-AXLE LOW-FLOOR SPECIAL CARGO WAGON FOR THE TRANSPORT OF TRUCKS WITH TRAILERS

S	plato-vagon s okretnim postoljem
	flat wagon with bogies
aa	sa 8 osovina ili više
	with 8 axles or more
d	za prijevoz cestovnih vozila, jednopodni
	transport of road vehicles, single decker
k	max. opterećenje tu < 50 t
	max. payload tu < 50 t
m	iskoristiva duljina vagona $18\text{ m} \leq l_u < 22\text{ m}$
	usable length of the wagon $18\text{ m} \leq l_u < 22\text{ m}$
s	max. brzina 100 km/h
	max. speed 100 km/h
z	prtvrdna kočnica
	ground-operated hand brake



8-OSOVINSKI NISKOPODNI SPECIJALNI TERETNI VAGON ZA PRIJEVOZ KAMIONA S PRIKOLICOM

8-AXLE LOW-FLOOR SPECIAL CARGO WAGON FOR THE TRANSPORT OF TRUCKS WITH TRAILERS

Tehnički podaci / Technical details	S ugrađenom zakretnom čelnom gredom	Bez zakretne čelne grede
	With built-in pivoting front beam	Without pivoting front beam
Duljina preko odbojnika	19995 mm	19590 mm
Length over buffers		
Broj osovina	8	
No. of axles		
Prosječna vlastita masa vagona	20 t	19 t
Average tare weight		
Nosivost vagona	44 t	
Max. payload		
Ukupna masa vagona	64 t	63 t
Total wagon weight		
Tip okretnog postolja	ML-T-029	
Boogie type		
Razmak osovina u okretnom postolju	750-700-750 mm	
Axle distance in a boogie		
Tip zračne kočnice	KE-GP-A 2x8"	
Air brake type		
Tip kočnog umetka	s diskovima (ferode)	
Brake block category		
Promjer kotača	380 mm	
Wheel diameter		
Duljina utovarne površine	18600 mm	19000 mm
Loading length		
Širina traga	2560 mm	
Track width		
Širina staze	880 mm	
Path width		
Razmak između staza	800 mm	
Distance between paths		
Visina staza od gornjeg ruba tračnice	470 mm	
Floor height from top of the rail		

